




- ◆ Clockwise or anti-clockwise operation
- ◆ Unit: N.m, in.lb, ft.lb, kg.cm
- ◆ Peak or real-time working mode
- ◆ Automatic power off
- ◆ With calibration certificate


VIDEO

TW200

unit: mm


SPECIFICATION

Code	TW12	TW20	TW30	TW135	TW200	TW340	TW550	TW850	TW1500	TW2000
Range(N.m)	2.4 ~ 12	4 ~ 20	6 ~ 30	27 ~ 135	40 ~ 200	68 ~ 340	110 ~ 550	170 ~ 850	300 ~ 1500	400 ~ 2000
Resolution	0.01N.m	0.01N.m	0.1N.m	0.1N.m	1N.m	1N.m	1N.m	1N.m	1N.m	1N.m
Accuracy	Clockwise	±3%	±3%	±2%	±2%	±2%	±2%	±2.5%	±2.5%	±2.5%
	Anti-clockwise	±4%	±4%	±3%	±3%	±3%	±3%	±3.5%	±3.5%	±3.5%
Size of square drive	1/4"	1/4"	1/4"	3/8"	1/2"	1/2"	3/4"	3/4"	1"	1"
Length(L)	390mm	390mm	390mm	415mm	530mm	650mm	950mm	1220mm	1800mm	1800mm
Weight	900g	900g	900g	950g	1400g	1800g	3400g	4400g	13kg	14kg
Power	2xAA batteries									

TORQUE