


- ◆ Reading mode: auto-read and continuous-read
- ◆ With temperature compensation (automatic/manual)
- ◆ With auto-hold feature
- ◆ Cell constant is adjustable
- ◆ One point calibration with standard
- ◆ Data capacity: 200 sets
- ◆ IP65 dust/waterproof
- ◆ Auto power off level



wristband (included)



standard solution(included)



SPECIFICATION

Conductivity	Range	0.00µS/cm~200mS/cm
	Resolution	0.01µS/cm minimum
	Electronic unit accuracy	±1.0%FS
	Measurement accuracy	±1.5%FS
	Reference temperature	25°C/77°F
	Calibration point	1
	Standard recognition	84µS/cm, 1413µS/cm, 12.88mS/cm
TDS	Range	0.00mg/L~300g/L
	Resolution	0.01mg/L minimum
	Accuracy	±1.0%FS
Temperature	Range	-5~110°C/23~230°F
	Resolution	0.1°C/0.2°F
	Accuracy	±0.4°C/±0.7°F
Input		electrode with 5-pin aviation connector
Power supply		rechargeable battery
Dimension		80x225x35mm
Weight		400g

INCLUDED ACCESSORIES

Main unit	1pc
Electrode	1pc
Electrode holder	2pcs
Wristband	1pc
Silicone rubber case	1pc
AC/DC adapter and charging cable	1pc
Standard solution	1bottom

