



- ◆ Based on HL scale, converted to other hardness scales (HV, HB, HRC, HRB, HS) and tensile strength MPa
- ◆ Impact direction can be set
- ◆ With average value calculation function
- ◆ Automatic power off
- ◆ Conforms to the standard ASTM A956-02
- ◆ With manufacturer inspection certificate



VIDEO

### SPECIFICATION

<b>Resolution</b>	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa
<b>Accuracy</b>	±6HLD/0.6HRC(HLD=800)
<b>Min. workpiece weight</b>	5kg (directly)
	2kg (on solid support)
	0.1kg (coupled on large plate)
<b>Min. workpiece thickness</b>	5mm
<b>Min. workpiece diameter</b>	22mm
<b>Max. workpiece surface roughness</b>	1.6μm(Ra)
<b>Power</b>	3 x AAA batteries
<b>Dimension</b>	150 × 80 × 24mm



### INCLUDED ACCESSORIES

<b>Main unit</b>	1pc
<b>Test block</b>	1pc
<b>Small support ring</b>	1pc
<b>Brush</b>	1pc
<b>USB cable</b>	1pc
<b>Batteries</b>	3pcs