



- ◆ Split type contact points
- ◆ Accuracy (without indicator):  
3μm (measuring range 0.95~ 10mm),  
4μm (measuring range 10~ 20.6mm)
- ◆ Repeatability (without indicator): 1μm
- ◆ Dial indicators are optional

Setting ring (optional)



Optional indicators (optional)



Code	Range	Quantity of points	Measuring range of point	Measuring depth (L1)	Total length (L)	Material of points	Type of point	Setting ring (optional)
240-014-11	0.95-1.55	5	0.95-1.15	13	89	carbide	A	Ø1
			1.07-1.25	13	89	carbide	A	Ø1.1
			1.17-1.35	13	89	carbide	A	Ø1.2
			1.27-1.45	13	89	carbide	A	Ø1.3
			1.37-1.55	13	89	carbide	A	Ø1.4
240-040-11	1.5-4.2	10	1.5-1.9	17	93	carbide	A	Ø1.75
			1.8-2.2	17	93	carbide	A	Ø2
			2.05-2.45	17	93	carbide	A	Ø2.25
			2.3-2.7	25	101	carbide	A	Ø2.5
			2.55-2.95	25	101	carbide	A	Ø2.75
			2.8-3.2	25	101	carbide	A	Ø3
			3.05-3.45	25	101	carbide	A	Ø3.25
			3.3-3.7	25	101	carbide	A	Ø3.5
			3.55-3.95	25	101	carbide	A	Ø3.75
			3.8-4.2	25	101	carbide	A	Ø4
			0.95-1.15	13	89	carbide	A	1
			1.07-1.25	13	89	carbide	A	Ø1.1
			1.17-1.35	13	89	carbide	A	Ø1.2



Code	Range	Quantity of points	Measuring range of point	Measuring depth (L1)	Total length (L)	Material of points	Type of point	Setting ring (optional)
240-040-12	0.95-4.2	15	1.27-1.45	13	89	carbide	A	Ø1.3
			1.37-1.55	13	89	carbide	A	Ø1.4
			1.5-1.9	17	93	carbide	A	Ø1.75
			1.8-2.2	17	93	carbide	A	Ø2
			2.05-2.45	17	93	carbide	A	Ø2.25
			2.3-2.7	25	101	carbide	A	Ø2.5
			2.55-2.95	25	101	carbide	A	Ø2.75
			2.8-3.2	25	101	carbide	A	Ø3
			3.05-3.45	25	101	carbide	A	Ø3.25
			3.3-3.7	25	101	carbide	A	Ø3.5
			3.55-3.95	25	101	carbide	A	Ø3.75
240-075-11	4.15-7.8	7	3.8-4.2	25	101	carbide	A	Ø4
			4.15-4.8	41	118	hard chromed	B	Ø4.5
			4.7-5.3	41	118	hard chromed	B	Ø5
			5.2-5.8	41	118	hard chromed	B	Ø5.5
			5.7-6.3	41	118	hard chromed	B	Ø6
			6.2-6.8	41	118	hard chromed	B	Ø6.5
			6.7-7.3	41	118	hard chromed	B	Ø7
240-120-11	7.7-12.5	6	7.2-7.8	45	118	hard chromed	C	Ø7.5
			7.7-8.3	45	118	hard chromed	C	Ø8
			8.2-8.8	45	118	hard chromed	C	Ø8.5
			8.7-9.3	45	118	hard chromed	C	Ø9
			9.2-10.5	45	118	hard chromed	C	Ø10
			10.2-11.5	45	118	hard chromed	C	Ø11
240-120-12	4.15-12.5	13	11.2-12.5	45	118	hard chromed	C	Ø12
			4.15-4.8	41	118	hard chromed	B	Ø4.5
			4.7-5.3	41	118	hard chromed	B	Ø5
			5.2-5.8	41	118	hard chromed	B	Ø5.5
			5.7-6.3	41	118	hard chromed	B	Ø6
			6.2-6.8	41	118	hard chromed	B	Ø6.5
			6.7-7.3	41	118	hard chromed	B	Ø7
			7.2-7.8	45	118	hard chromed	C	Ø7.5
			7.7-8.3	45	118	hard chromed	C	Ø8
			8.2-8.8	45	118	hard chromed	C	Ø8.5
			8.7-9.3	45	118	hard chromed	C	Ø9
			9.2-10.5	45	118	hard chromed	C	Ø10
			10.2-11.5	45	118	hard chromed	C	Ø11
240-200-11	12.2-20.6	8	11.2-12.5	45	118	hard chromed	C	Ø12
			12.2-13.5	45	118	hard chromed	C	Ø13
			13.4-14.6	45	118	hard chromed	C	Ø14
			14.4-15.6	45	118	hard chromed	C	Ø15
			15.4-16.6	45	118	hard chromed	C	Ø16
			16.4-17.6	45	118	hard chromed	C	Ø17
			17.4-18.6	45	118	hard chromed	C	Ø18
			18.4-19.6	45	118	hard chromed	C	Ø19
19.4-20.6	45	118	hard chromed	C	Ø20			