## **CFN1500B**


## **COATING THICKNESS GAUGE**











- F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel) N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
- ◆ Large display screen
- ◆ V-type probe to make the cylinder measurement easier
- With um/mil unit conversion
- ◆ Automatic power on/ off
- With back light
- With manufacturer inspection certificate

## **SPECIFICATION**

SFECIFICATION.		
Range	0~1500μm	
Accuracy	2μm(0~100μm)	
	3%(100~1500μm)	
Resolution	0.1µm (0~99.9µm)	
	1μm (100~1500μm)	
Min. measuring area	25×25mm	
Min. curvature	convexity: 5mm; concave: 30mm	
Min substrate thickness	magnetic material: 0.2mm; non magnetic material: 0.05mm	
Memory	30 sets	
Powersupply	AAA batteries	
Dimension(L×W×H)	120×52×26mm	
Weight	170g	



## **INCLUDED ACCESSORIES**

Main unit	1pc
Calibration foil	1set
Calibration base	1set
AAA battery	2pcs