



- ◆ F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic substrates (iron, steel)

N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive substrates (zinc, copper, aluminum)

- ◆ External interchangeable probe
- ◆ Single and continuous working mode
- ◆ Low and high limits setting with judgement
- ◆ With average calculation
- ◆ With comparison measurement function
- ◆ With temperature compensation
- ◆ Turn off automatically
- ◆ With manufacturer inspection certificate



VIDEO



CN1500

SPECIFICATION

Code	CF1500H	CF1500	CN1500	CFN1500
Probe type	F		N	F and N
Range	0 ~ 1500μm			
Accuracy	2μm (0 ~ 100μm)			
	2%(100 ~ 1500μm)			
Resolution	0.1μm (0 ~ 999μm)			
	1μm (1000 ~ 1500μm)			
Memory	500			
Working temperature	-10°C~150°C	-10°C~50°C		
Power	3×AAA batteries			
Dimension(L×W×H)	150×50×29mm			
Weight	170g			

INCLUDED ACCESSORIES

Main unit	1pc
Calibration foil	1set
Calibration base	1set
USB cable	1pc
AAA battery	3pcs