







- ◆ Conforms to ISO868, ISO7619, ASTM D 2240
- ◆ Testing time is adjustable
- ◆ With average calculation function
- ◆ With manufacturer inspection certificate


**VIDEO**

**HS5D indenter**

**HS1A indenter**

**HSOO indenter**

**HS1A**

**Standard block (included)**

**PR100 printer (optional)**

**Standard (optional)**
**SPECIFICATION**

Code	HS1A	HS5D	HSOO
Scale	HA(Shore A)	HD(Shore D)	HOO(Shore OO)
For material	soft plastic, rubber, leather, etc.	hard plastic, hard rubber, etc.	soft sponge, soft rubber, etc.
Measuring range	20 ~ 90HA	20 ~ 90HD	20 ~ 90HOO
Resolution	0.1HA	0.1HD	0.1HOO
Accuracy	±1HA	±1HD	±1HOO
Indenter protrusion	2.5mm		
Power	rechargeable battery		
Weight	180g		

**INCLUDED ACCESSORIES**

Main unit	1pc
Standard block	1pc
Charger	1pc
Software	1pc

**OPTIONAL ACCESSORIES**

Printer	PR100
Stand for HS1A	HS-1A-STD
Stand for HS5D	HS-5D-STD
Stand for HSOO	HS-OO-STD