



◆ Large screen of the read out



VIDEO



PP3015

OPTIONAL ACCESSORIES




20X, 50X, 100X  
lens with half-reflection mirror (glass diameter 100mm, graduation 2°)




rotary table




5X magnifier



Series 552 glass scale




holder with clamp



swivel center support









V-block with clamp



Overlay chart



**SPECIFICATION**

Code	PP3015	PP3020
X-Y stage travel	150×50mm	200×100mm
Metal stage size	340×152mm	400×225mm
Glass stage size	195×95mm	245×145mm
Screen diameter	diameter: Ø300mm	
Image	inverted	
Linear scale resolution	1µm	
Accuracy	(4+L/25)µm L is the measuring length in mm	
Z(focus) travel range	80mm	
Max. load capacity	4kg	
Rotation scale	range: 0°~360°, resolution: 1' or 0.01°, accuracy: 6'	
Magnification accuracy	±0.1%	
Illumination	contour illumination: 12V/100W halogen lamp, 2-step(high/low) brightness adjustment	
	surface illumination: 24V/150W halogen lamp	
Readout display	X-Y stage travel, screen rotation	
Output	RS232 and USB	
Readout functions	 measure coordinate of point	
	 measure coordinate of line	
	 measure center coordinate, radius of circle with three points	
	 measure distance between two objects	
	 measure angle with four points or two lines	
	 coordinate transform	
Dimension (L×W×H)	480×780×1150mm	
Weight	135kg	

**INCLUDED ACCESSORIES**

Main unit	1pc
10X lens with half-reflection mirror	1pc
Overlay chart clip	4pcs
Level	1pc
Anti-dust cover	1pc

**OPTIONAL ACCESSORIES**

20X lens with half-reflection mirror	PP3000-LENS20X
50X lens with half-reflection mirror	PP3000-LENS50X
100X lens with half-reflection mirror	PP3000-LENS100X
Rotary table	PP3000-TABLE
5X magnifier	PP3000-MAGNIFIER
Holder with clamp	PP3000-HOLDER
Swivel center support	PP3000-SUPPORT
V-block with clamp	PP3000-VBLOCK
Calibration scale	Series 552(refer to page 285)
Overlay chart	PP3015-CHART