

SERIES TW

DIGITAL TORQUE WRENCH




- ◆ Clockwise or anti-clockwise operation
- ◆ Unit: N.m, in.lb, ft.lb, kg.cm
- ◆ Peak or real-time working mode
- ◆ Automatic power off
- ◆ With calibration certificate



TW200

unit: mm



SPECIFICATION

***NEW**

| Code | TW12 | TW20 | TW30 | TW135 | TW200 | TW340 | TW550 | TW850 | TW1500 | TW2000 |
|----------------------|----------------|---------|--------|----------|----------|----------|-----------|-----------|------------|------------|
| Range(N.m) | 2.4 ~ 12 | 4 ~ 20 | 6 ~ 30 | 27 ~ 135 | 40 ~ 200 | 68 ~ 340 | 110 ~ 550 | 170 ~ 850 | 300 ~ 1500 | 400 ~ 2000 |
| Resolution | 0.01N.m | 0.01N.m | 0.1N.m | 0.1N.m | 1N.m | 1N.m | 1N.m | 1N.m | 1N.m | 1N.m |
| Accuracy | Clockwise | ±3% | ±3% | ±2% | ±2% | ±2% | ±2% | ±2.5% | ±2.5% | ±2.5% |
| | Anti-clockwise | ±4% | ±4% | ±3% | ±3% | ±3% | ±3% | ±3.5% | ±3.5% | ±3.5% |
| Size of square drive | 1/4" | 1/4" | 1/4" | 3/8" | 1/2" | 1/2" | 3/4" | 3/4" | 1" | 1" |
| Length(L) | 390mm | 390mm | 390mm | 415mm | 530mm | 650mm | 950mm | 1220mm | 1800mm | 1800mm |
| Weight | 900g | 900g | 900g | 950g | 1400g | 1800g | 3400g | 4400g | 13kg | 14kg |
| Power | 2xAA batteries | | | | | | | | | |



AECUD